

LG Chemical Limited LG Twin Tower / East Wing 20, Yoido-dong, Youngdungpo-gu Seoul 150-721 Korea

Ingestion

Inhalation

Chronic Effects

Mutagenicity

Tel: 822-3773-7449, 3634 Fax: 822-3773-7692, 7652

MSDS

(MATERIAL SAFETY DATA SHEET)

Grade 80HF SAN RESIN

File Number	MSDS- SAN 80HF
Issue Date	1997. 04. 12
Revised Date	1999. 08. 20
Revised Item	
Page	1/3

	Fax:	822-3773-7692, 7652		Page	1/3
1.	Chem	nical Product & Manufacturer's Information	on		
	a. b. c. d. e. Ingree a. b. c.	Chemical Product Name Usage Chemical Type Manufacturer's Address Prepared By	Acrylonitrile Styrene Co-polymer Electronic Goods, Automotive Part Thermoplastics LG Chem, 20, Yoido-dong, Younge LG Chem / ABS PS Division CAS Number		
3.	d. e. f. Physi	cal & Chemical Character			
	a. b. c. d.	Appearance Odor pH Specific Gravity	Pellet Almost Odorless Neutral 1.07		
	e. f. g. h.	Evaporation Rate Vapor Pressure Vapor Density Solubility in Water Solubility in other Solvent	Not applicable at standard condition Not applicable at standard condition Not applicable at standard condition insoluble Soluble in THF, Acetone and other	n n	vents
4.	Healt	h Hazard Data			
	a. b.	Threshold Limit Effect of overexposure - Eye Contact - Skin Contact	Solid or dust may cause irritation o mechanical action Essentially nonirritating to skin, Me		
		- Skin Absorption	Unlikely due to physical properties	Shamour mjury C	~··· ,

Unlikely due to physical state.

may cause respiratory irritation

Not Available Not Available

Dust may cause irritation to respiratory

In case of breathing, fumes released from heated material



MSDS

Grade: 80HF

File Number	MSDS- SAN 80HF
Revised Date	1999. 08. 20
Page	2/3

5	First	hiA	Measures
υ.	IIIOL	/\IU	Micagaics

a. Eye Contact Immediately rinse eyes with copious amount of running water

and seek medical advice

b. Skin Contact Essentially nonirritating to skin but rinse with copious water

c. Ingestion If vomiting occurs, lower the head to ease vomiting and seek for medical

advice

d. Inhalation In case of breathing, fumes released from heated material may

cause respiratory irritation

In case of inhaling dense smoke, immediately remove a person to fresh air. If necessary, apply artificial respiration

and seek medical attention immediately

e. Mutagenicity Not Available

6. Fire & Explosion Hazard Data

a. Flash Point Not Applicable

b. Flammability 1/16" HB (UL-94, File No. E67171M)

c. Auto Ignition Point Not Applicable

d. Extinguishing Media Usually use water and use extinguishing media appropriate to

surrounding conditions

e. Special Fire Fighting Procedure Cool Containers with water spray. In closed stores, provide fire

fighter with self-contained breathing apparatus in positive

pressure mode

f. Usual Fire and Explosion Hazards Irritating gases and dense smoke

7. Reactivity Data

a. Stability Stable under normal condition
 b. Storage conditions to avoid Avoid fire and heating above 60°C

c. Incompatibility None known
 d. Hazardous decomposition products
 e. Hazardous polymerization Not occur

8. Spill or Leak Procedures

a. Cleaning Method Sweep, use vacuum cleaner, or shovel into intact packaging

for waste disposal or possible re-use

b. Waste Disposal Method Reuse or transfer to an approved disposal area.

Observe all federal, state, or local regulations upon disposition



MSDS

Grade: 80HF

File Number	MSDS- SAN 80HF
Revised Date	1999. 08. 20
Page	3/3

Орс	cial Protection Information	
a.	Eye	Safety goggles
b.	Hands	Protective gloves
b.	Respirator	Chemical protect respirator (fumes released from heated material)
C.	Others	If necessary, use protective equipment handling this product
.Han	dling & Storage	
a.	Handling	Avoid formation of dust
		Keep bags always closed / Keep container lightly closed
		Avoid pellets / bags from getting wet
	Storage	Keep bags / containers in a well-ventilated place
b.		Avoid pellets / bags from getting wet

Product should be handled, stored, and used in accordance with the generally accepted industrial hygiene practices and in conformity with all the applicable legal regulations. The information provided herein is based on the knowledge possessed at this present time from the view point of safety requirements. It should, therefore, not be construed as guaranteeing specific properties.